

D20NXP / D25NXP / D30NXP / D33NXP / D35NXP G20NXP / G25NXP / G30NXP / G33NXP / G35NXP

NX PLUS SERIES FORKLIFTS

Pneumatic Diesel & LPG 2.0 to 3.5 ton capacity Euro Stage V



Everything has changed. New NXP, the game changer.

Experience the fully enhanced value of the NXP Series

The new NXP Series offers excellent power, durability and high operator comfort. Keeping the customer satisfied is our main focus, and this is guaranteed by offering the best productivity and convenience in a variety of industrial applications.

MAXIMUM PRODUCTIVITY

• The combination of a powerful engine and a rigid transaxle provides a gradeability with load of 25%.

 With the optimised Doosan hydraulic system, the NX Plus series has an unbeatable travel/lifting speed.



NEW SLEEK DESIGN

Doosan created a **new design** that fits the Doosan tradition of delivering simple, powerful performance, represented in an upgraded exterior.



■ NXP Diesel



OPTIMAL ERGONOMICS


- Plenty of legroom which gives the operator the necessary comfort while driving.
- The clearance and angle of the acceleration and brake pedals are positioned to minimise ankle fatigue.
- The neatly arranged hydraulic hoses and chains provide clear front visibility through the wide view mast.
- The compact steering wheel allows quick control and reduces wrist fatigue.
- Front/rear visibility has increased by improving the design of the operator compartment and counterweight.

EXCELLENT RELIABILITY

- The new auxilary weight design lowers the centre of gravity and helps reduce noise, vibration and heat.
- The cooling capacity has increased by optimising the air flow of the engine room and the design of the counter weight.
- The design of the anti-dust head guard and dual element air cleaner extend the service interval and guarantees the durability of engine.
- The mast has a higher stiffness, which makes the operation more stable.

Maximum productivity

The combination of a powerful engine transmission and drive axle maximises the performance and gives you the best productivity in every application.





Kubota V2403-CR-TE5B Diesel Engine

The Kubota V2403-CR Diesel engine delivers powerful performance and generates capacity through key temperature control technology. It also increases the ash cleaning and engine oil change interval, resulting in TCO optimization.



Kubota WG2503-L LPG-motor

The Kubota WG2503 engine will get the work done at any given load condition maintaining a flat torque curve. It also accomplishes both durability and low noise, complying with Euro Stage V.



Powerful Gradeability

With the powerful engine, transmission and auxilary weight structure, the maximum gradeability is optimised and it is easy to drive up 25% (3.0t, @1.6 km/h) steep slopes.

"Boost your productivity with Doosan"



Wide Mast Visibility

The neatly arranged hydraulic hoses and chains provide clear front visibility through the wide view mast.



Outstanding Stability

The new auxilary weight lowers the centre of gravity and enables you to lift big loads, ideal for use in heavy load applications.



High Speed of Lifting / Lowering

The gear pump and mast regulator valve are optimised to increase the lifting/lowering speed, which boosts the effiency of your forklift.

Safety

The NX Plus series is equipped with various safety features. It helps prevent accidents, ensuring safety of the employees and people in the surrounding area.





Rearranging of Tilt Cylinder

The tilt cylinder was removed from the floor plate to prevent the driver from falling over it.



Operator Sensing System (OSS)

Whenever the operator leaves the seat, the truck travel and mast lifting functions will stop. This system avoids any unintended forklift movements when the operator is not seated.

- Warning when the operator leaves the seat without setting the parking brake.
- Warning when the operator drives without the seatbelt fastened.
- Automatically stops the vehicle when the operator leaves the seat.



Large Entry Grip Bar

The entry grip bar is larger, making it easy to grasp and enabling safer mounting on/off the truck.



ISO3691 Hydraulic Locking Valve

When the operator leaves the truck unattended, the hydraulic locking system prevents unintentional lowering and tilting of the mast. It safeguards the truck, the load and the work array.



Large panoramic mirror

Provides a clear view of the rear working area for the operator, to ensure safe working conditions.



Anti-slip Step Plate

The wider step plate prevents slipping and it also helps safer mounting on/off the truck.



LED lights

Brighter and last longer than traditional sealed beams or halogen lights.

" Doosan takes safety to the next level"

Optimal ergonomics

The operator compartment is spacious and ergonomically designed to reduce operator fatigue. It allows for greater comfort and safe operation.




"Infinite adjustability, optimised controllability and exceptional reliability makes Doosan the operator's first choice."




Small steering wheel

The steering wheel has a compact design that reduces operator fatigue.



Steering Column & Instrument Panel Offset

Steering column is shifted to the left for more comfortable posture. Instrument panel is also shifted to the right for easier viewing.



Spacious Legroom

The knee clearance is widened and the tilt cylinder is removed on the floor plate. Acceleration and brake pedal clearance and angle are improved to reduce ankle fatigue.



Adjustable Tilt Steering Column

The steering column can be adjusted over a wide range of angles, allowing an optimal posture for the operator.



Extended Steering Angle

The turning radius is improved by increasing the steering angle. The NXP series makes it easy to manoeuvre in confined spaces.



Integrated Lamp Switch

The turn signal and head lamp switches are integrated for convenient operation.




Improved Front / Rear Visibility


The improvement of the cowl height (-40 mm) and counter weight design has increased front and rear visibility and enables safer driving.



Excellent reliability

The NXP series is equipped with an advanced design to reduce noise, vibration, heat and dust inflow, ensuring durability of key components. With the improved design and extra heavy duty options, the NXP ensures durability in harsh operating conditions.





Optimized Air Flow

The airflow is optimised by improving the position of the muffler, increasing the space between the parts and increasing the inner space of the counterweight. It streamlines the airflow and increases the cooling capacity.



Auxilary Weight

Many troubles are caused by vibration. The engine is mounted on the auxilary weight to effectively absorb vibration and suppress noise. This extends parts durability and prevents durability decline and oil leakage.



Anti Dust Design

The bottom-sealed overhead guard eliminates the dust inflow from the bottom side.



Robust Mast

The reinforcement rib (J-channel) of the mast beam improves mast stiffness and lateral stability. The six roller carriage provides superior strength and durability for wider and longer loads.



Dual Elements Air Cleaner

The air cleaner with dual element filter protects the engine against dust effectively, ensuring the durability of engine. This is standard on the NX Plus series.



Pre-cleaner OPTION


In a dusty environment, the pre-cleaner removes the dust beforehand and effectively extends the life of the air cleaner.



"The robustness of the Doosan truck gets the job done."

Minimised Total Cost of Ownership

Doosan ensures maximum uptime of your truck by providing low maintenance forklifts, minimising your total cost of ownership.



Diesel Particulate Filter (DPF)

In order to comply with Euro Stage V, it was necessary to equip our diesel forklifts with a Diesel Particulate filter. Doosan believes it is important to maximise the uptime of your truck, so we have made sure that service is reduced to a minimum. Regeneration is automatic.



What is the downtime of the forklift when regenerating?

In a normal operation, the regeneration takes place during driving so you won't even notice it is being done. In a light application, a manual (also referred to as "forced") regeneration might be needed and it takes about 40 minutes. This forced regeneration is only possible when the coolant temperature is above 40 degrees (the coolant temperature can be checked on the monitor). Since this is a high-temperature regeneration, it is recommended to consider the surrounding environment during regeneration.



After approximately how many hours do I need to regenerate?

The regeneration will take place during normal operation without you being aware of it. Only in light applications, a manual regeneration process might be needed every 50 to 100 working hours. You can predict the need for manual regeneration based on the soot meter on the monitor.



What kind of service costs are involved?

DPF does not need to be replaced long as it is regenerated regularly. You just detach the DPF and do ash cleaning regularly every 5000 hours.




Can I postpone the regeneration to a more suitable time?

Yes. You can put the regeneration off by using the 'inhibit switch'. However, if the soot exceeds 110%, the power will be limited to alert you to regenerate and avoid harm to the DPF.



After how many hours do I need a new DPF?

As long as you follow the regeneration and ash cleaning instructions, there is no need for a new DPF. We advise you to avoid using so-called DPF cleaning additives as they can harm your DPF beyond repair.



Energy saving


- The G25NX Plus Series meets the Euro Stage V standards thanks to its catalytic muffler.
 The engine is environmentally clean and very powerful.
- The D25NX Plus Series is equipped with an electronic engine wich consumes less than the mechanical engine of the D25GX Plus Series.

Longer Service Interval

The diesel NX Plus series reduces maintenance costs and extends life in the field, significantly minimising total cost of ownership.

Great Serviceability

Doosan offers an excellent service. Our NX Plus series has been designed with maintenance in mind and can be serviced fast and easy.





Worldwide service network






Doosan Genuine Parts

The parts warehouse supplies high quality Doosan parts to your local dealer.



Junction Box


The fuse and relay are centralised for easy maintenance.




Hood Locking Cylinder

Helps easy maintenance and helps prevent accidents.









Main Specifications

MAJOR SPECIFICATIONS		DG20NXP	DG25NXP
Load capacity/rated load	kg	2,000	2,500
Load centre	mm	500	500
Load distance, centre of drive axle to fork	mm	472	472
Wheelbase	mm	1,700	1,700
Height, mast lowered	mm	2,045	2,045
Free Lift	mm	150	150
Lift (with STD 2-stage mast)	mm	3,000	3,000
Height, mast extended	mm	4,247	4,247
Height of overhead guard	mm	2,160	2,160
Height of seat	mm	1,185	1,185
Overall Length	mm	3,610	3,660
Length to fork face	mm	2,560	2,610
Overall width	mm	1,290	1,290
Turning radius	mm	2,280	2,330

Standard Features and Optional Extras

SAFETY & STABILITY	Diesel	LPG
Operating Sensing System (OSS)		
Back up Alarm - Inside		
Control valve with hydraulic locking		
Rear safety light		
Rear grab handle with horn switch		
Static ground strap		
Strobe light		
Autoshift controller		
Ground Speed Control		
Spark arrestor		

* Remark : This list is based on factory data.
Standard or optional can vary for specific countries.

OPERATOR COMFORT (ERGONOMICS)	Diesel	LPG
Clear front/rear mast visibility		
LED combination lights		
Entry grab bar		
Anti-slip step plate		
Panoramic mirror		
Integrated lamp switch		
Compact steering wheel with steering knob		
Clip board		
Modular cabin - Type A,B,C		
Full cabin (with heater & air conditioner)		
Cup holder		
USB port		
Fuel cap with key		
Operator fan		

DG30NXP	DG33NXP	DG35NXP
3,000	3,300	3,500
500	500	500
472	477	477
1,700	1,700	1,700
2,045	2,045	2,045
150	150	150
3,000	3,000	3,000
4,247	4,252	4,252
2,160	2,160	2,160
1,185	1,185	1,185
3,715	3,780	3,800
2,665	2,730	2,750
1,290	1,290	1,290
2,415	2,460	2,480



PRODUCTIVITY	Diesel	LPG
Auxilary weight		
Power shoe brakes		

RELIABILITY	Diesel	LPG
Mast with JJ beam		
Anti dust overhead guard		
Dual element air cleaner		
Pre-cleaner		

SERVICEABILITY	Diesel	LPG
Toolless side panel		
Toolless floor plate		
Hood locking cylinder		
Junction box		



EUDG25NXP-200616v1EN (June 2020)



Doosan Industrial Vehicles UK Limited

12 Kilvey Road Brackmills Industrial Estate Northampton NN4 7BQ

Tel.:01604 825 600 Website:www.doosanflt.com

Authorized Dealer		